| BROACHING TOOL WITH ADJUSTABLE CUTTING BLADES  |  |
|--|--|
| Patent Number:   | ☐ <u>US5120166</u>   |
| Publication date:  | 1992-06-09   |
| Inventor(s):   | WOERNER JOHANN (DE)  |
| Applicant(s):  | WIDIA HEINLEIN GMBH (DE)   |
| Requested Patent:  | ☐ <u>DE3922963</u>   |
| Application Number:  | US19900551438 19900710   |
| Priority Number(s):  | DE19893922963 19890712   |
| IPC Classification:  | B23P15/42  |
| EC Classification:   | B23D37/00B, B23D43/06  |
| Equivalents:   | ☐ <u>EP0407907</u> , <u>B1</u> , ES2056307T, JP3084049B2, ☐ <u>JP3117510</u> |
| Abstract   |  |
| A broaching tool has at least one adjustable cutting blade or plate. A two-fold adjustment is possible by mounting each cutting blade on an upper section of an insert mounted in a recess of a support or support ring sector. The upper insert section is secured to a lower insert section. The lower insert section is radially adjustable. The upper insert section is axially adjustable. Each adjustment can be made independently of the other adjustment. |  |
| Data supplied from the esp@cenet database - I2   |  |